



PRODUCT INFORMATION SHEET

Component Transmitter or Receiver for Wireless Audio Links

Part Number WALTX/RX

Image



Description NOTE: All performance parameters were measured in accordance with TIA/EIA-603 procedures unless otherwise specified.

Table with General Performance section containing various technical specifications like System Description, Frequency Range, and Sensitivity.

Table with Audio section containing Input and Output specifications for Audio Interface Types, Audio Interface Level, and Audio Line Distortion.

Environmental

All products described are subject to availability based on manufacturing capacity and shipping dates. While every effort has been made to ensure the accuracy of all information, ISS does not accept liability for any errors or omissions and reserves the right to change information as needed.

© 2015 Information Station Specialists, Inc. All rights reserved.



PRODUCT INFORMATION SHEET

Operating Temperature:	-22°F to +140°F (-30°C to +60°C) @ 100% duty cycle
Supply Requirements:	10.5V - 16DC
DC Current: Low Power Tx High Power Tx Rx (2W Speaker Output) Rx Muted	25W TB7100: 3.1A (5W) 6.3A (25W) 540mA 280mA
Dimensions:	18.8 x 15.7 x 1.8in (480mm x 400mm x 44.5mm) 1U rack space
Weight:	13.2lb (6kg)

Options
Internal AC PSU (99-264 VAC)
External T809-10 PSU (88-264 VAC)
Wall Mount Bracket
Microphone

All products described are subject to availability based on manufacturing capacity and shipping dates. While every effort has been made to ensure the accuracy of all information, ISS does not accept liability for any errors or omissions and reserves the right to change information as needed.

© 2015 Information Station Specialists, Inc. All rights reserved.